Company	THE INTERCLAY PETROLEUM CORPORATION
Well	A. L. BLUNDON No. 1
Field	CHAVES CO.
County	CHAVES CO.
State	NEW MEXICO
Location	1980' S & 1980' W OF SE CORNER SEC. 10, T-8-S, R-25-E
Elevation	K.B. 3966' D.F. 3965' G.L. 3956'
Date	10-2-1964
Run No.	ONE
Depth Driller	6500'
Depth Logger	6500'
Bottom Log Interval	6500'
Top Log Interval	2000'
Casing Driller	8-5/8" @ 1000'
Casing Logger	NONE
Bit Size	7-7/8"
Type Fluid in Hole	LIME MUD
Density	9.4
Viscosity	45
Fluid Loss	8.0
Source of Sample	PITS
Rm @ Meas. Temp.	.75 @ 75°
Rmf @ Meas. Temp.	.60 @ 75°
Rmc @ Meas. Temp.	.90 @ 75°
Source Rmf / Rmc	CALCULATED
Rm @ BHT	.35 @ 130°
Time Since Circ.	12 HRS.
Time Logger on Bottom	1:00 A.M.
Equipment No.	1-1
Recorded By	J. ROSS
Witnessed By	MR. WOOTEN

DUAL INDUCTION - LATERLOG

SPONTANEOUS POTENTIAL millivolts | CONDUCTIVITY millimhos/m or $\mu mho/m$ | RESISTIVITY ohms m²/m | M NORMAL | INDUCTION | LATERLOG

Company	THE INTERCLAY PETROLEUM CORPORATION
Well	A. L. BLUNDON No. 1
Field	CHAVES CO.
County	CHAVES CO.
State	NEW MEXICO
Location	1980' S & 1980' W OF SE CORNER SEC. 10, T-8-S, R-25-E
Elevation	K.B. 3966' D.F. 3965' G.L. 3956'
Date	10-2-1964
Run No.	ONE
Depth Driller	6500'
Depth Logger	6500'
Bottom Log Interval	6500'
Top Log Interval	2000'
Casing Driller	8-5/8" @ 1000'
Casing Logger	NONE
Bit Size	7-7/8"
Type Fluid in Hole	LIME MUD
Density	9.4
Viscosity	45
Fluid Loss	8.0
Source of Sample	PITS
Rm @ Meas. Temp.	.75 @ 75°
Rmf @ Meas. Temp.	.60 @ 75°
Rmc @ Meas. Temp.	.90 @ 75°
Source Rmf / Rmc	CALCULATED
Rm @ BHT	.35 @ 130°
Time Since Circ.	12 HRS.
Time Logger on Bottom	1:00 A.M.
Equipment No.	1-1
Recorded By	J. ROSS
Witnessed By	MR. WOOTEN

DETAIL LOG

SPONTANEOUS POTENTIAL millivolts | CONDUCTIVITY millimhos/m or $\mu mho/m$ | RESISTIVITY ohms m²/m | M NORMAL | INDUCTION | LATERLOG

SPONTANEOUS POTENTIAL millivolts | CONDUCTIVITY millimhos/m or $\mu mho/m$ | RESISTIVITY ohms m²/m | M NORMAL | INDUCTION | LATERLOG

HEADERSTATION ANALYSIS

Data was checked against the original field log and found to be correct. Depth corrections were made where necessary and the data was edited to remove spikes and erroneous readings.

The depth scale for Headerstation measurements that field which was used for field prints.

Run	Depth Driller	Depth Logger	Bottom Log Interval	Casing Driller	Casing Logger
1	6500'	6500'	6500'	8-5/8" @ 1000'	NONE
2	6500'	6500'	6500'	NONE	NONE
3					

Run	Type Log	Depth Scale Used	Time Since Circ.	Max. Rec. Temp.	Equipment No.	Location
1	DIL	5"	12 HRS.	130°	1-1	1980' S & 1980' W OF SE CORNER SEC. 10, T-8-S, R-25-E
2	DIL	2"	12 HRS.	130°	1-1	1980' S & 1980' W OF SE CORNER SEC. 10, T-8-S, R-25-E
3						